

# ROUGHNECK

## Tiller, Center Console, Side Console & Tunnel Jet

### All-Welded Jon Series



TILLER MODEL - R1760



SIDE CONSOLE MODEL - R1760SC



CENTER CONSOLE MODEL - R1760CC



TUNNEL JET MODEL - R1860CJ



SPECIAL BAY MODEL - RV190BAY

#### KEY FEATURES

- VorTrac™ 3 1/2° or 8 Degree Hull
- Oversize Floor Rivets
- Extruded Receiver Gunnel
- Extruded Center Keel
- Recessed Cleats
- Navigation Lights
- Powerful Bilge Pump
- Large 44" Long, 23 Gallon Livewell\*
- X-Long Rod / Gun Locker\*
- Heavy-Duty Console\*
- Massive Dry Storage
- X-Strong Trolling Motor Deck
- Olive Drab Paint

#### KEY OPTIONS

- Camo, Silver, Black, Red or White Paint
- Gator-Skin™ Interior Coating
- Motor Guide® FW46FB Trolling Motor
- Motor Guide® FW54FB Trolling Motor
- Pedestal Seats

#### RECEIVER GUNNEL OPTIONS

- Mr. Crappie Pro-Series Rod Holder
- Rod Holder Extension
- Rod Holder w/ Side Mount
- Cup Holder w/ Side Mount
- Locking Surface Mount
- Dog Platform\*

\* Available on Select Models

**As Tough As You Are** From panfish to large mouth and mallards to Canadas, these versatile, easy-on-the-budget boats have gained a reputation for being one of the toughest you can buy. Choose either a 3 1/2° VorTrac™ performance hull, or 8° VorTrac II™ big-water hull, both with durable 5052 H-34 all-welded construction and TufDeck™ aluminum floor liners for years of fishing and hunting action.



### 3 1/2° Performance Hulls

	LENGTH	BEAM	SIDE DEPTH	BOTTOM WIDTH	TRANSOM HEIGHT	APPROX. HULL WT.	MAX. WT. CAP.	PERSON CAP.	MAX. HP CAP.	MAX. PERSON WT. CAP.	HULL GAUGE	PKG. LENGTH
R1455	14' 7"	79"	25"	55"	20"	510 lb	1,100 lb	4	40 hp	599 lb	.100"	19'
	4.45m	2.01m	.64m	1.40m	.51m	231 kg	499 kg		30 kw	272 kg	2.5mm	5.79m
R1455SC	14' 7"	79"	25"	55"	20"	560 lb	1,100 lb	4	50 hp	599 lb	.100"	19'
	4.45m	2.01m	.64m	1.40m	.51m	254 kg	499 kg		37 kw	272 kg	2.5mm	5.79m
R1655	16' 5"	79"	25"	55"	20"	658 lb	1,360 lb	5	50 hp	750 lb	.100"	19' 2"
	5.00m	2.01m	.64m	1.40m	.51m	298 kg	617 kg		37 kw	340 kg	2.5mm	5.84m
R1655SC	16' 5"	79"	25"	55"	20"	752 lb	1,360 lb	5	75 hp	750 lb	.100"	19' 2"
	5.00m	2.01m	.64m	1.40m	.51m	341 kg	617 kg		56 kw	340 kg	2.5mm	5.84m
R1655CC	16' 5"	79"	25"	55"	20"	769 lb	1,360 lb	5	75 hp	750 lb	.100"	19' 2"
	5.00m	2.01m	.64m	1.40m	.51m	348 kg	617 kg		56 kw	340 kg	2.5mm	5.84m
R1760	17' 6"	83.5"	25"	60"	20"	782 lb	1,550 lb	6	60 hp	990 lb	.100"	19' 2"
	5.33m	2.12m	.64m	1.52m	.51m	354 kg	703 kg		45 kw	449 kg	2.5mm	5.84m
R1760SC	17' 6"	83.5"	25"	60"	20"	876 lb	1,550 lb	6	75 hp	990 lb	.100"	19' 2"
	5.33m	2.12m	.64m	1.52m	.51m	397 kg	703 kg		56 kw	449 kg	2.5mm	5.84m
R1760CC	17' 6"	83.5"	25"	60"	20"	888 lb	1,550 lb	6	75 hp	990 lb	.100"	19' 2"
	5.33m	2.12m	.64m	1.52m	.51m	403 kg	703 kg		56 kw	449 kg	2.5mm	5.84m
R1760CJ	17' 6"	83.5"	25"	60"	20"	839 lb	1,550 lb	6	80 hp	990 lb	.100"	19' 2"
	5.33m	2.12m	.64m	1.52m	.51m	381 kg	703 kg		60 kw	449 kg	2.5mm	5.84m
R1860	18' 5"	83.5"	25"	60"	20"	850 lb	1,680 lb	7	60 hp	1,078 lb	.110"	21' 2"
	5.61m	2.12m	.64m	1.52m	.51m	386 kg	762 kg		45 kw	489 kg	2.8mm	6.45m
R1860SC	18' 5"	83.5"	25"	60"	20"	956 lb	1,680 lb	7	90 hp	1,078 lb	.110"	21' 2"
	5.61m	2.12m	.64m	1.52m	.51m	434 kg	762 kg		67 kw	489 kg	2.8mm	6.45m
R1860CC	18' 5"	83.5"	25"	60"	20"	956 lb	1,680 lb	7	90 hp	1,078 lb	.110"	21' 2"
	5.61m	2.12m	.64m	1.52m	.51m	434 kg	762 kg		67 kw	489 kg	2.8mm	6.45m
R1860CJ	18' 5"	83.5"	25"	60"	20"	962 lb	1,680 lb	7	90 hp	1,078 lb	.110"	21' 2"
	5.61m	2.12m	.64m	1.52m	.51m	436 kg	762 kg		67 kw	489 kg	2.8mm	6.45m
R2065	19' 9"	88"	25"	65"	20"	1,006 lb	1,898 lb	8	75 hp	1,258 lb	.110"	21' 2"
	6.02m	2.24m	.64m	1.65m	.51m	456 kg	861 kg		56 kw	571 kg	2.8mm	6.45m
R2065SC	19' 9"	88"	25"	65"	20"	1,110 lb	1,898 lb	8	115 hp	1,258 lb	.110"	21' 2"
	6.02m	2.24m	.64m	1.65m	.51m	503 kg	861 kg		86 kw	571 kg	2.8mm	6.45m
R2065CC	19' 9"	88"	25"	65"	20"	1,112 lb	1,898 lb	8	115 hp	1,258 lb	.110"	21' 2"
	6.02m	2.24m	.64m	1.65m	.51m	504 kg	861 kg		86 kw	571 kg	2.8mm	6.45m
RV160	16'	76.5"	19.5"	52"	20"	654 lb	1,100 lb	4	50 hp	550 lb	.100"	XXX"
	4.88m	1.94m	.50m	1.32m	.51m	297 kg	499 kg		37 kw	249 kg	2.5mm	XXXm
RV160SC	16'	76.5"	19.5"	52"	20"	704 lb	1,100 lb	4	50 hp	550 lb	.100"	XXX"
	4.88m	1.94m	.50m	1.32m	.51m	319 kg	499 kg		37 kw	249 kg	2.5mm	XXXm
RV160CC	16'	76.5"	19.5"	52"	20"	704 lb	1,100 lb	4	50 hp	550 lb	.100"	XXX"
	4.88m	1.94m	.50m	1.32m	.51m	319 kg	499 kg		37 kw	249 kg	2.5mm	XXXm
RV170	17' 3"	85.5"	19.5"	60"	20"	739 lb	1,110 lb	4	60 hp	650 lb	.100"	XXX"
	5.26m	2.17m	.50m	1.52m	.51m	335 kg	503 kg		45 kw	295 kg	2.5mm	XXXm
RV170SC	17' 3"	85.5"	19.5"	60"	20"	789 lb	1,110 lb	4	75 hp	650 lb	.100"	XXX"
	5.26m	2.17m	.50m	1.52m	.51m	358 kg	503 kg		56 kw	295 kg	2.5mm	XXXm
RV170CC	17' 3"	85.5"	19.5"	60"	20"	789 lb	1,110 lb	4	75 hp	650 lb	.100"	XXX"
RV170Bay	5.26m	2.17m	.50m	1.52m	.51m	358 kg	503 kg		56 kw	295 kg	2.5mm	XXXm
RV190	18' 5"	85.5"	19.5"	60"	20"	830 lb	1,290 lb	4	75 hp	650 lb	.100"	XXX"
	5.61m	2.17m	.50m	1.52m	.51m	376 kg	581 kg		56 kw	295 kg	2.5mm	XXXm
RV190SC	18' 5"	85.5"	19.5"	60"	20"	880 lb	1,290 lb	4	115 hp	650 lb	.100"	XXX"
	5.61m	2.17m	.50m	1.52m	.51m	399 kg	581 kg		86 kw	295 kg	2.5mm	XXXm
RV190CC	18' 5"	85.5"	19.5"	60"	20"	880 lb	1,290 lb	4	115 hp	650 lb	.100"	XXX"
RV190Bay	5.61m	2.17m	.50m	1.52m	.51m	399 kg	581 kg		86 kw	295 kg	2.5mm	XXXm

### 8° Big-Water Hulls